

# 2021 Mirage

## FEATURES AND OPTIONS



2021 MIRAGE	TECHNICAL AND MECHANICAL FEATURES			
Feature Description	ES	LE	Carbonite Edition (CE)	SE
<b>Engine</b>				
Type	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder
Engine Code	3A92	3A92	3A92	3A92
Materials	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block
Bore x Stroke	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm
Compression Ratio	10.5:1	10.5:1	10.5:1	10.5:1
Displacement	1.2L / 1193 cc	1.2L / 1193 cc	1.2L / 1193 cc	1.2L / 1193 cc
Horsepower	78PS,76hp@6000	78PS,76hp@6000	78PS,76hp@6000	78PS,76hp@6000
Torque	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm
Emissions	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70
Fuel System	ECI-MULTI	ECI-MULTI	ECI-MULTI	ECI-MULTI
<b>Transmission</b>				
5 Speed Manual Transmission	STD	-	-	-
1st	3.545	-	-	-
2nd	1.913	-	-	-
3rd	1.31	-	-	-
4th	0.973	-	-	-
5th	0.804	-	-	-
Reverse	3.214	-	-	-
Final Drive	4.055	-	-	-
INVECS-III CVT	OPT	STD	STD	STD
CVT Automatic Ratios	4.007 - 0.550	4.007 - 0.550	4.007 - 0.550	4.007 - 0.550
Reverse	3.771	3.771	3.771	3.771
Final Drive	3.757	3.757	3.757	3.757
<b>Suspension</b>				
Front	MacPherson type strut	MacPherson type strut	MacPherson type strut	MacPherson type strut
Rear	Torsion Beam	Torsion Beam	Torsion Beam	Torsion Beam
<b>Steering</b>				
Type	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist
Turn Circle - Curb to Curb (ft)	30.2 ft.	30.2 ft.	30.2 ft.	30.2 ft.
Turn Circle - Wall to Wall (ft)	32.1 ft.	32.1 ft.	32.1 ft.	32.1 ft.
<b>Brakes/ Tires/ Wheels</b>				
Front	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc
Rear	Drum Brake	Drum Brake	Drum Brake	Drum Brake
Anti-Lock Brakes	STD	STD	STD	STD
Wheels	14-inch steel wheels with wheel covers	14-inch alloy wheels	14-inch alloy wheels	15-inch two-tone alloy wheels
Tires	165/65R14	165/65R14	165/65R14	175/55R15
Spare Tire (Temporary Tire)	STD	STD	STD	STD
<b>Exterior Dimensions</b>				
Wheelbase (inches)	96.5	96.5	96.5	96.5
Length (inches)	151.4	151.4	151.4	151.4
Width (inches)	65.6	65.6	65.6	65.6
Height (inches)	59.4	59.4	59.4	59.4
Track, Front (inches)	56.3	56.3	56.3	56.3
Track, Rear (inches)	55.7	55.7	55.7	55.7
Min. Ground Clearance (inches)	6.3	6.3	6.3	6.3
<b>Interior Dimensions</b>				
<b>Head Room</b>				
Front Head Room (inches)	39.0	39.0	39.0	39.0
Rear Head Room (inches)	37.2	37.2	37.2	37.2
<b>Leg room</b>				
Front Leg Room (inches)	41.7	41.7	41.7	41.7
Rear Leg Room (inches)	34.2	34.2	34.2	34.2
<b>Shoulder room</b>				
Front Shoulder Room (inches)	51.7	51.7	51.7	51.7
Rear Shoulder Room (inches)	51.0	51.0	51.0	51.0
<b>Hip room</b>				
Front Hip Room (inches)	48.8	48.8	48.8	48.8
Rear Hip Room (inches)	46.4	46.4	46.4	46.4
<b>SAE volume</b>				
Interior Volume (cu. ft.)	103.3	103.3	103.3	103.3
Passenger Volume (cu. ft.)	86.2	86.2	86.2	86.2
Cargo volume (rear seats up) (cu. ft.)	17.1	17.1	17.1	17.1
Cargo volume (rear seats down) (cu. ft.)	47.0	47.0	47.0	47.0
<b>Capacities</b>				
Passenger Seating Capacity	5	5	5	5
Fuel Tank Capacity	9.2 gal	9.2 gal	9.2 gal	9.2 gal
<b>Weights</b>				

2021 MIRAGE		TECHNICAL AND MECHANICAL FEATURES			
Feature Description	ES	LE	Carbonite Edition (CE)	SE	
GVWR CVT [5MT]	3020 (2910)	3020	3020	3020	
Curb Weight CVT [5MT]	2095(2040)	2095	2095	2117	
<b>Fuel Economy</b>					
City (MT)	36 (33)	36	36	36	
Highway (MT)	43 (41)	43	43	43	
Combined (MT)	39 (36)	39	39	39	
<b>Electrical</b>					
Battery	55D23L	55D23L	55D23L	55D23L	
Alternator (Amps)	85 Amps	85 Amps	85 Amps	85 Amps	
<b>Warranties</b>					
Basic	5 years or 60,000 miles	5 years or 60,000 miles	5 years or 60,000 miles	5 years or 60,000 miles	
Powertrain	10 years or 100,000 miles	10 years or 100,000 miles	10 years or 100,000 miles	10 years or 100,000 miles	
Anti-corrosion	7 years or 100,000 miles	7 years or 100,000 miles	7 years or 100,000 miles	7 years or 100,000 miles	
Roadside Assistance	STD	STD	STD	STD	
	A03AXNMHL2M (01) A03AXTMHL2M (11)	A03AXTMHL2M (11)	A03AXTMHL2M (11)	A03AXTPHL2M (15)	

2021 MIRAGE		TECHNICAL AND MECHANICAL FEATURES			
Feature Description	ES	LE	Carbonite Edition (CE)	SE	
<b>Engine</b>					
Type	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	1.2 L MIVEC DOHC, 12-valve Inline 3-cylinder	
Engine Code	3A92	3A92	3A92	3A92	
Materials	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block	Aluminum Head/ Aluminum Block	
Bore x Stroke	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm	75.0 mm x 90.0 mm	
Compression Ratio	10.5:1	10.5:1	10.5:1	10.5:1	
Displacement	1.2L / 1193 cc	1.2L / 1193 cc	1.2L / 1193 cc	1.2L / 1193 cc	
Horsepower	78PS,76hp@6000	78PS,76hp@6000	78PS,76hp@6000	78PS,76hp@6000	
Torque	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm	74 lb.-ft. @ 4000 rpm	
Emissions	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70	Tier 3 Bin 70 LEV III ULEV70	
Fuel System	ECI-MULTI	ECI-MULTI	ECI-MULTI	ECI-MULTI	
<b>Transmission</b>					
5 Speed Manual Transmission	STD	-	-	-	
1st	3.545	-	-	-	
2nd	1.913	-	-	-	
3rd	1.31	-	-	-	
4th	0.973	-	-	-	
5th	0.804	-	-	-	
Reverse	3.214	-	-	-	
Final Drive	4.055	-	-	-	
INVECS-III CVT	OPT	STD	STD	STD	
CVT Automatic Ratios	4.007 - 0.550	4.007 - 0.550	4.007 - 0.550	4.007 - 0.550	
Reverse	3.771	3.771	3.771	3.771	
Final Drive	3.757	3.757	3.757	3.757	
<b>Suspension</b>					
Front	MacPherson type strut	MacPherson type strut	MacPherson type strut	MacPherson type strut	
Rear	Torsion Beam	Torsion Beam	Torsion Beam	Torsion Beam	
<b>Steering</b>					
Type	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist	Rack-and-pinion, Electric Power Assist	
Turn Circle - Curb to Curb (ft)	30.2 ft.	30.2 ft.	30.2 ft.	30.2 ft.	
Turn Circle - Wall to Wall (ft)	32.1 ft.	32.1 ft.	32.1 ft.	32.1 ft.	
<b>Brakes/ Tires/ Wheels</b>					
Front	Ventilated disc	Ventilated disc	Ventilated disc	Ventilated disc	
Rear	Drum Brake	Drum Brake	Drum Brake	Drum Brake	
Anti-Lock Brakes	STD	STD	STD	STD	
Wheels	14-inch steel wheels with wheel covers	14-inch alloy wheels	14-inch alloy wheels	15-inch two-tone alloy wheels	
Tires	165/65R14	165/65R14	165/65R14	175/55R15	
Spare Tire (Temporary Tire)	STD	STD	STD	STD	
<b>Exterior Dimensions</b>					
Wheelbase (inches)	96.5	96.5	96.5	96.5	
Length (inches)	151.4	151.4	151.4	151.4	
Width (inches)	65.6	65.6	65.6	65.6	
Height (inches)	59.4	59.4	59.4	59.4	
Track, Front (inches)	56.3	56.3	56.3	56.3	
Track, Rear (inches)	55.7	55.7	55.7	55.7	
Min. Ground Clearance (inches)	6.3	6.3	6.3	6.3	
<b>Interior Dimensions</b>					
<b>Head Room</b>					
Front Head Room (inches)	39.0	39.0	39.0	39.0	
Rear Head Room (inches)	37.2	37.2	37.2	37.2	
<b>Leg room</b>					
Front Leg Room (inches)	41.7	41.7	41.7	41.7	
Rear Leg Room (inches)	34.2	34.2	34.2	34.2	
<b>Shoulder room</b>					
Front Shoulder Room (inches)	51.7	51.7	51.7	51.7	
Rear Shoulder Room (inches)	51.0	51.0	51.0	51.0	
<b>Hip room</b>					
Front Hip Room (inches)	48.8	48.8	48.8	48.8	
Rear Hip Room (inches)	46.4	46.4	46.4	46.4	
<b>SAE volume</b>					
Interior Volume (cu. ft.)	103.3	103.3	103.3	103.3	
Passenger Volume (cu. ft.)	86.2	86.2	86.2	86.2	
Cargo volume (rear seats up) (cu. ft.)	17.1	17.1	17.1	17.1	
Cargo volume (rear seats down) (cu. ft.)	47.0	47.0	47.0	47.0	
<b>Capacities</b>					
Passenger Seating Capacity	5	5	5	5	
Fuel Tank Capacity	9.2 gal	9.2 gal	9.2 gal	9.2 gal	

2021 MIRAGE	TECHNICAL AND MECHANICAL FEATURES			
Feature Description	ES	LE	Carbonite Edition (CE)	SE
<b>Weights</b>				
GVWR CVT [5MT]	3020 (2910)	3020	3020	3020
Curb Weight CVT [5MT]	2095(2040)	2095	2095	2117
<b>Fuel Economy</b>				
City (MT)	36 (33)	36	36	36
Highway (MT)	43 (41)	43	43	43
Combined (MT)	39 (36)	39	39	39
<b>Electrical</b>				
Battery	55D23L	55D23L	55D23L	55D23L
Alternator (Amps)	85 Amps	85 Amps	85 Amps	85 Amps
<b>Warranties</b>				
Basic	5 years or 60,000 miles	5 years or 60,000 miles	5 years or 60,000 miles	5 years or 60,000 miles
Powertrain	10 years or 100,000 miles	10 years or 100,000 miles	10 years or 100,000 miles	10 years or 100,000 miles
Anti-corrosion	7 years or 100,000 miles	7 years or 100,000 miles	7 years or 100,000 miles	7 years or 100,000 miles
Roadside Assistance	STD	STD	STD	STD
	A03AXNMHL2M (01) A03AXTMHL2M (11)	A03AXTMHL2M (11)	A03AXTMHL2M (11)	A03AXTPHL2M (15)